

SMARTUBE^{RS}

THE FASTEST SMARTUBE

SELLING POINTS

ROLLING SPEED

LIGHTNESS

PROTECTION



DESCRIPTION

Smartube RS – Redefining Inner Tube Performance

Introducing the all-new **Smartube RS**: engineered to be up to **26.5% faster** than its predecessor, lighter, and featuring enhanced puncture protection. Thanks to a brand-new formulation, it sets a new standard—delivering unmatched performance, reliability, and versatility.

Whether you're using **Tube Type** or **Tubeless Ready (TLR)** tires, Smartube RS integrates seamlessly into your setup. Testing proves it offers rolling speeds comparable to sealant-based tubeless systems—without the mess or maintenance.

No compromises. No complications. Just pure speed, made simple.

Pair it with our **P ZERO Race RS** tires for the fastest, most efficient system we've ever created.



ROLLING RESISTANCE



LIGHTWEIGHT CONSTRUCTION



AIR RETENTION



HIGH PUNCTURE PROTECTION

DETAILS



Presta valve: mechanism with glued core, different lengths to work with the majority of rim depths, black colour to look clean and slick

For SmartUBE RS:



DO NOT USE if bike is equipped with RIM Brakes.

DO NOT REPAIR replace if tube or valve is damaged.

TECH OVERVIEW

1 Material



NEW (TPU) thermoplastic polyurethane



Further development of our TPU material, now with even lower hysteresis for lower rolling resistance, at the same weight and compact volume.



UP TO **26.5 %** FASTER THAN SMARTUBE

PRODUCT	SETTING	WEIGHT (g)	PUNCTURE PROTECTION THICKNESS (mm)
Butyl	25/32-622	125	16,7
Latex	30/38-622	80	29
Smartube	23/32-622	35	17
Smartube RS	26/35-622	32	22,5



LIGHTER AND MORE PUNCTURE PROTECTED

2 Comparison

	REFERENCE	SETTING	TOTAL SYSTEM WEIGHT (g)	ROLLING RESISTANCE*	SMARTUBE RS is:
TUBE TYPE	PZERO RS Tubetype 28-622 (230g)	Butyl	355	14.3 W	<ul style="list-style-type: none"> • 24.3% faster than butyl • 14% faster than Smartube
		Smartube	266	13.1 W	
		Smartube RS	262	11.5 W	
TLR	PZERO RS TLR 28-622 (290g)	Sealant (40 ml)	340	9.6 W	<ul style="list-style-type: none"> • As fast as TLR, with less hassle • 26.5% faster than Smartube
		Smartube	326	12.4 W	
		Smartube RS	322	9.8 W	

*Test conducted at usage pressure at 28 km/h

4 Range

Product Name	Size	ETRTO	Valve type	IP CODE	Weight
PZERO SmarTUBE RS 26/35-622 42mm	700x26/35C	26/35-622	Presta 42mm Black	4727900	32g
PZERO SmarTUBE RS 26/35-622 60mm	700x26/35C	26/35-622	Presta 60mm Black	4728100	33g
PZERO SmarTUBE RS 26/35-622 80mm	700x26/35C	26/35-622	Presta 80mm Black	4728000	34g